



EC TYPE EXAMINATION (MODULE B)

CERTIFICATE No. MED013120CS/002

This is to certify that RINA Services S.p.A. (Notified Body No. 0474) did undertake the relevant type approval procedures for the equipment identified below, which was found to be in compliance with the Fire Protection requirements of Marine Equipment Directive (MED) 2014/90/EU, including the requirements and testing standards of Regulation (EU) 2019/1397.

<i>MED Item N°</i>	MED/3.18a
<i>USCG Category N°</i>	164.112
<i>Description</i>	Surface materials and floor coverings with low flame-spread characteristics: (a) decorative veneers
<i>Type</i>	DPS-DECORATIVE STICKER
<i>Applicant</i>	DPS TECHNOLOGY & COLORS SRL P.ZZA RISORGIMENTO 21 20831 Seregno (MB) ITALY
<i>Testing standards</i>	IMO Res. MSC.307(88)-(2010 FTP Code)
<i>Reference standards</i>	Chap. II-2 and X of SOLAS 74 Convention, as amended, RINA Rules for the certification of Marine Equipment

Issued in Genoa on
January 17, 2020

This Certificate is valid until
May 20, 2024

This Certificate consists of this sheet plus an attachment

Enrico Cabella
RINA Services S.p.A.

This document is a copy of a digitally signed file available on Rina Web Site: <http://www.rina.org>



ATTACHMENT TO
CERTIFICATE No. MED013120CS/002

Page 1 of 2

Manufacturer

DPS TECHNOLOGY & COLORS SRL

Place of Manufacturer

VIA DELL'INDUSTRIA 4/6
20833 Giussano (MB)
ITALY

Product description

Decorating System composed of 2 layers:

1st layer: satin epoxy primer called "EPOXY GC007" produced by GRIGNACOLOR SRL. Di CASTELNUOVO GIUSEPPE & C. – Ballabio (LC) or COLORSYSTEM VERNICI SRL – CANTU' (CO) (thickness range 0.031 – 0.047 mm and mass per area range 81 - 123 g/m²);

2nd layer: self-adhesive film called "Wrapcast CW/990-FT", produced by HOUSE COPIES SAS – Seregno (MB) (thickness 0.207 mm and mass per area of 260 g/m²).

Primer thickness (average value) (mm) 0.038

Film thickness (mm) 0.207 ± 20%

Primer mass per area (average value) (g/m²) 103

Film mass per area (g/m²) 260 ± 10%

Field of application

As material for all exposed interior and concealed or inaccessible surfaces.

When intended for bulkhead and ceiling the product may be applied to any metallic support having a thickness ≥ 0.56 mm. When intended for deck the product may be applied to any non-combustible support, any metallic support or any material having low flame spread characteristics.

On the basis of the value of the total heat release (Q_t) and on the basis of the value of the peak heat release (q_p) the material is deemed not generating excessive quantities of smoke nor toxic products in fire according to Annex 2 IMO 2010 FTP Code.

Tests carried out


Tests as per RINA Test Laboratory reports Nos. 2019CS011501/1, 2019CS011501/2 and 2019CS011501/3 dated 21 May 2019 issued according to:

- IMO 2010 FTP Code Part 5
- ISO 1716: 2010

This certificate annuls and replaces the certificate No. MED150119CS dated 05/21/2019 due to entry of USCG category number.

This document is a copy of a digitally signed file available on Rina Web Site: <http://www.rina.org>

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production control phase module (D, E or F) of Annex II of the Directive is fully complied with a written inspection agreement with a Notified Body



XXXX/YYYY

"WHEELMARK FORMAT"

XXXX *Notified Body number undertaking surveillance module*

YY *Last two digits of year mark affixed*

USCG Approval

This product has been assigned a U.S. Coast Guard module B number (*USCG number: 164.112/EC0474*) to note type approval to Module B only as it pertains to obtaining U.S. Coast Guard approval as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment" as amended by Decision N. 1/2018 signed on 18th February 2019.

The manufacturer is allowed to affix the U.S. Coast Guard approval number to the above equipment subject to the authorization of the Notified Body undertaking the surveillance module.

General conditions for the approval

- a) The initial conditions verified by RINA at the time of the approval are to be maintained
- b) Any changes to the initial conditions are to be promptly communicated to RINA, which reserves the right to repeat the relevant assessment
- c) This certificate will no be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with RINA
- d) RINA personnel are to be allowed to witness during the performances of activities, upon their request
- e) The activities are to be carried out in compliance with the RINA Rules and/or other applicable Rules
- f) Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply.



Enrico Cabella

This document is a copy of a digitally signed file available on Rina Web Site: <http://www.rina.org>